SEIKA	AKU TE	ECHNIC	AL GROUP	LIMITE	D	
客	È					
料	號	NF05840				
р рр	名	說明書-英文	Ź			
規	格	DANTE32S	_V1.0			
公司機種(客户機	(種)成品料號	DM48.20				
重量/	基數	0.03KG/1				
材	質	NH00231 1	1:2			
紙張展	開性質		4 ■A5 □其它		紙張展開]數量 4pcs
核准		審核	校稿		製稿	研發部 2022.07.05 馮斌
產品文件	·編號:					
陽片數量	:8張	單位:mm	公差:±3mm			





User's Manual

High Performance Networking Audio Transceiver Module





Important Safety Instructions



This symbol, wherever used, alerts you to the presence of un-insulated and dangerous voltages within the product enclosure. These are voltages that may be sufficient to constitute the risk of electric shock or death.

This symbol, wherever used, alerts you to important operating and maintenance instructions.

Please read.

Protective Ground Terminal

AC mains (Alternating Current)

AC mains (Alternating Current)

Denotes the product is turned on.

OFF: Denotes the product is turned off.

WARNING

Describes precautions that should be observed to prevent the possibility of death or injury to the user.

CAUTION

 \sim

ON:

Describes precautions that should be observed to prevent damage to the product. Disposing of this product should not be placed in municipal waste but rather in a separate collection.

WARNING

Power Supply

Ensure that the mains source voltage (AC outlet) matches the voltage rating of the product. Failure to do so could result in damage to the product and possibly the user. Unplug the product before electrical storms occur and when unused for long periods of time to reduce the risk of electric shock or fire.

External Connection

Always use proper ready-made insulated mains cabling (power cord). Failure to do so could result in shock/death or fire. If in doubt, seek advice from a registered electrician.

Do Not Remove Any Covers

Within the product are areas where high voltages may present. To reduce the risk of electric shock do not remove any covers unless the AC mains power cord is removed. Covers should be removed by qualified service personnel only.

No user serviceable parts inside.

Fuse

To prevent fire and damage to the product, use only the recommended fuse type as indicated in this manual. Do not short circuit the fuse holder. Before replacing the fuse, make sure that the product is OFF and disconnected from the AC outlet.

Protective Ground

Before turning the unit ON, make sure that it is connected to Ground. This is to prevent the risk of electric shock. Never cut internal or external Ground wires. Like wise,

never remove Ground wiring from the Protective Ground Terminal

Notas

Operating Conditions

Always install in accordance with the manufacturer's instructions.

To avoid the risk of electric shock and damage, do not subject this product to any liquid/rain or moisture. Do not use this product when in close proximity to water

Do not install this product near any direct heat source. Do not block areas of ventilation. Failure to do so could result in fire. Keep product away from naked flames.

IMPORTANT SAFETY INSTRUCTIONS

Read these instructions Follow all instructions Keep these instructions. Do not discard. Heed a warnings. Only use attachments / accessories specified by the manufacturer.

Power Cord and Plug

Do not tamper with the power cord or plug. These are designed for your safety. Do not remove Ground connections! If the plug does not fit your AC out let seek advice from a qualified electrician. Protect the power cord and plug from any physical stress to avoid risk of electric shock. Do not place heavy objects on the power cord. This could cause electric shock or fire.

Cleaning

When required, either blow off dust from the product or use a dry doth. Do not use any solvents such as Benzol or Alcohol. For safety, keep product clean and free from dust.

Servicina

Refer all servicing to gualified service personnel only. Do not perform any servicing other than those instructions contained within the User's Manual.





Λ	Notas	Index
-		- 1.INTRODUCTION4
		- 2.INSTALLATION5
		- 3.NOTAS
		-
		-
		-
		-
		-
		-
		-
		-
		-
		-
		-
		-
		-
		-
		-
		-

DANTEBES

DANTE325

Introduction

1. Feature summary

- Redundant network connections via switch
- Bit depths: 32 per sample
- Up to 32*32 channels at 48kHz
- Up to 32*32 simultaneous audio streams
- High-quality, low jitter on-board clock
- Up to 2000 sample audio buffering per channel
- Software is upgradable over network

2. Temperature Charateristics

- Operating temperature range: 0° to 70° Celsius
- Recommended storage temperature: -40° to +100° Celsius

3. Electrical Characteristics

- Power Supply: 3.3V
- Power Consumption: < 2W

4. Interface function instruction

The ACT/LINK port that connects DANTE and PC can play and record in 32 channels.

Driver install

2). Settings

NOTE: Most settings cannot be changed while Dante Virtual Soundcard is running, or when an ASIO application is connected.

NOTE: The device name and audio interface (sample rate and bit depth) must be set in Dante Controller, While Dante Virtual Soundcard is running.

To change settings:

- Completely quit out of any audio applications that are using the Dante Virtual Soundcard.
- b. Stop Dante Virtual Soundcard
- c. Change your Dante Virtual Soundcard settings.
- d. Restart Dante Virtual Soundcard
- e. Restart your audio application/s.

Click Settings on Dante Virtual Soundcard Control Panel and set up paremeters as below:

Setting: Licensing About	DV5: ASIO Options
Acidlo ASIC ▼ Uptions	Buffer Size: 512 - samples
Audio Chernelis: S2 × 32 ▼	Encoding: 32 - bits / samp
Dante Latency: Gims ▼	Axin Latency: 10 - mx
Network: Status: _GObcs	OK

NOTE: Computer with poor scheduling performance will need to use higher settings of Buffer.

Size and Asio Latency.

Click Start to start the Dante Virtual Soundcard. When the button shows Stop, it indicates that the Dante Virtual Soundcard is currently running. The icon shows Start, illustrating the Dante Virtual Soundcard is currently stopped. Click the button to toggle the running state of Dante.



DANTE32S



Driver install

- Dante Virtual Soundcard

1). Starting the Dante Virtual Soundcard Control Panel (Windows) By default , Dante Virtual Soundcard will be installed in: C:\Program Files\Audinate\ Dane Virtual Soundcard\In 64-bit Windows, it will appear under C: \Program Files (x86).

The Dante Virtual Soundcard Control Panel can be started in one of two ways: One: using the Start menu: Start>Programs>Audinate>Dante Virtual Soundcard>Dante Virtual Soundcard; or Windows 8: Windows key>Dante Virtual Soundcard

Two: navigate to the directory where it is installed, and double-click the Dante

Virtual Soundcard icon: 🔬 dvs_gui.exe

The first time you start the Dante Virtual Soundcard Control Panel, you will be presented with the Licensing screen.

👲 Dante Virtual Soundcard	X
Settings Licensing About	
Enter a License ID:	Get a License
	Start

Once you have obtained a License ID, it can be entered in the Licensing tab. The Activate button is not enabled until a correctly formatted License ID has been entered into the dialog box.

NOTE: Eusure that your computer has access to the Internet during this step.

🖉 Dante Virtual Soundcard	_ 🗆 🗙
Settings Licensing About	
Enter a License ID:	Get a License Activate
	Start

Installation

1). Disassemble the 2 screws by the screw driver following the below picture.



2). Disassemble the Module from MIXER.



3). Insert the Module on the slots following the below picture and the Module must be on the middle of the slot.



- 4). Push the module and make it matched with the whole panel .
- 5). Assemble the 2 screws following the below picture.





Driver install

5. Minimum System Requirement

The tables below list the minimum system specification for your computer to be able to use Dante Controller.

Disclaimer: It is possible that your computer may meet the requirements below, but suffer from some other individual performance limitation related to its particular hardware. Please seek the advice of your computer support administrator.

General

Component	Recommended Minimum Requirement
Processor	1GHz or better,Dual core CPU
Memory	1 Gigabyte of RAM
network	A Gigabit(1000 Mbps) Ethernet network interface is required for channel conuts above 32x32@48kHz. Wireless LAN(WiFi) Ethernet interfaces are not supported.
Operating System(Windows)	Windows 7 (SP1 and above), 8 and 8.1.NOTE:both UTF-8 and Unicode are supported EXCEPT for host or device names ; the DNS standard does not support Unicode for these
Storage /Disk	As is the case with any application of this type, higher transfer rates are required for recording and playing back large numbers of audio tracks to and from disk. Disk speeds of 7200rpm and above are recommended for more than 16 channels of record/playback from disk.

6. Softwares to be intalled

- Dante Controller

1). About Dante Controller

Dante Controller is a software application provided by Audinate which allows users to configure and route audio around Dante networks. It is available for Windows and OS X.

2). Installing Dante Controller NOTE: Before installing, please turn on Firewall. a. Double-click the icon for Dante Controller.exe

DanteController-3.5.6.2_windows.exe

Driver install



Select the device name of Dante Virtual Soundcard on the screen.



Click **Device Config** to display the configuration of Dante Virtual Soundcard and then change the setting of Dante Virtual Soundcard.

e Device	view Ha	1p	
2 28 19	•< 🕀	3311YM-11015556 *	
eceive Toa	nemit State	e Latency Device Coulig Network Coulig Bereboard	
(East	an Jesse		
	BK:	YN II 066536 Apply	
-	L. D		
Sur	ale run.		
	Sacht	Rene: 49k · Pull-mp/down: · ·	
		This device does not support	
		.'ull-cp/dom.configuration.	
[Eaco	diax		
	E00	00.141	
	The	dev et clota acti support.	
rDeni	en Tracorat	Loong on genn a	
00.0	of the second		
Сл	zest lateacy	1 a.w.	
	Latency	Maximum Natwork Siza	
0	150 usec	Singhist network with one covint.	
0	250 0:00	Singhist network with three evolutions	
0	500 uses	Gigabit converk with five switcher	
	l mero	Signisit notwork with ten switches or gigabit notwork with 100Mbps loof and re	
0	2 mos	Giaubit converts with 100Mino loaf acder	
0	5 mm	Safe wire	i

DANTE32S



2	Dr
9	

Driver install



Click [+] between different devices to show Tx channels and Rx channels, and click any grid between Tx channels and Rx channels to change the connected state of the two channels .

NOTE: There is no sense to click any grid between Tx channels and Rx channels of the same device.

File Device View Holp		
9回来品级王	Matter Clock Dr., V3 J 36c.;;	6
Division of the start Starts	Basest Saras Treat	
/2 Dante		R = 2
olas litrions	and the second s	
Doube Receivent		
dedart. 241,0 Copie Copie	0 0	
	e e	
1		
10-31	6 0	
1		

Next, configure audio interface and device name of Dante Virtual Soundcard using Dante Controller. By default, the device name of Dante Virtual Soundcard is user name of your computer.

Click Device button on Menu bar , you will be presented with the Device view.

Driver install

b. Read the license text, and if you accept the terms of the agreement, click the 'I Agree ...'check- box. If you don't accept the terms, click Close to termina te the installation.

2 Dante Controller Setup	×
Dante Controller	
END USER LICENSE AGREEMENT	-
NOTICE: CAREFULLY READ THE FOLLOWING LEGAL AGREEMENT WHICH CONTAINS RIGHTS AND RESTRUCTIONS ASSOCIATED WITH YOUR USE OF THE AUDINATE'S OFTWARE (THE 'SOFTWARE') AND DOCUMENTATION PROVIDED TO YOU BY AUDINATE PTY, LTD (THE 'LICENSOR'). INSTALLING OR	111
USING THE SOFTWARE CONSTITUTES YOUR ACCEPTANCE OF	ns
Sinstall Cto	ie

c. Acknowledge/accept any Windows security warning that are displayed. d. Click **Launch** to start Dante Controller or Click **Close** to finish installing.

🧕 Dante Controller Setup	
Dante Controller	
Setup Successful	
	Launch Close

- Dante Virtual Soundcard
- 1). About Dante Virtual Soundcard

Dante Virtual Soundcard is a software application that turns your PC or Mac into a Dante-enabled device, allowing Dante audio traffic to be transmitted and received using the standard Ethernet port. No additional hardware is required. NOTE: The Dante Virtual Soundcard does not support virtual machines - it must

be installed on a computer with a standard Windows or Mac OS X operating system .

DANTE32S

Driver install

 Installing Dante Virtual Soundcard NOTE: Before installing, please turn on Firewall. To install:

- a. Ensure you are logged on to your PC as an administrator.
- b. Double-click the icon for the Dante Virtual Soundcard.

DanteVirtualSoundcard-3.7.0.22_windows.exe

c. Read the license text, and if you accept the terms of the agreement, click the "I Agree ..."checkbox. If you do not accept the terms, click Close to terminate the installation.



d. The Network Throttling Management screen is displayed. Audinate advises that you let Dante Virtual Soundcard manage network throttling(the default option).

e. Click Install.



Driver install

f. Acknowledge/accept any Windows security warnings that are displayed. g. click Launch to start the software application or click Close to finish installing.

	Dante Virtual :	Soundcard	
Setup	Successful		
		Launch	Close

Audio Applications for recording and playback Please refer to 'operating_instructions_for_recording_and_playback.doc' file.

7. Configuration

- Dante Controller
- 1). Starting the Dante Controller

By default ,Dante Controller will be installed in:C:\Program Files\Audinate\ Dane controller\In 64-bit Windows, it will appear under C:\Program Files (x86). The Dante Controller can be started in several ways :

One: using the Start menu: Start>Programs>Audinate>Dante Controller> Dante Controller.

Two: navigate to the directory where it is installed, and double-click the Dante Controller.

② DanteController.exe

Routing:

When Dante Controller is started , it always displays the Routing Tab within the Network View. In this view the network is shown in the form of grid. Devixes with Tx channels are displayed along the top row of the grid, and those with Rx channels are displayed along the left-hand column of the grid. Initially a collapsed view is presented; individual channels cannot be seen.